



16 Payne Street, Park Rynie, 4182, South Africa

Telephone: (039) 9761114 | Facsimile: 086 535 7997  
e-mail: [james@butech.co.za](mailto:james@butech.co.za) | website: [www.butech.co.za](http://www.butech.co.za)

## Bu-Tack 1T HIGH QUALITY BUTYL

**Bu-Tack 1T** has been assessed, tested and approved by an independent Laboratory to NFRC Class "A" standard.

### GENERAL DESCRIPTION:

**Bu-Tack 1T** is a preformed high performance polyisobutylene (PIB) based sealing tape available in single strand or multi-lane rolls. This product has a multitude of applications where joints need to be formed to seal against air and water ingress. The product is cost effective, non-toxic and requires no tools to apply.

COLOURS	Black
DIMENSIONS	2mm to 35mm THICK, 5mm to 200mm wide. Roll length is dependent on thickness.
SHELF LIFE	24 Months in ambient conditions.
LIFE EXPECTANCY	In excess of 25 years.

U.V. RESISTANCE	Excellent.
SERVICE TEMPERATURE RANGE	-40 To +90°C.
JOINT MOVEMENT	Up to 15%
COMPATIBILITY	Very good adhesion to most surfaces & compatible with most commonly used construction materials. For further information, please contact our technical department.
MOISTURE VAPOUR TRANSMISSION RATE: INDEPENDENTLY TESTED TO BS 15106-3	0.003 g/m <sup>2</sup> /24hr/mm at 25 °C & 75% RH

### **PRODUCT DATA:**

### **FEATURES & BENEFITS:**

- \* SELF WOUND ROLL PRESENTATION
- \* SOLVENTLESS FORMULATION
- \* INSTANT SEAL
- \* DIRECT CONTROL OVER QUANTITY OF SEALANT USED IN THE JOINT
- \* ENVIRONMENTALLY FRIENDLY

\* EASE OF USE

\* GOOD ADHESION ON BOTH FACES TO MOST BUILDING MATERIALS

\*HIGH PUMPING RESISTANCE

### **APPLICATION:**

**Bu-Tack 1T** should be applied to surfaces at a temperature range of between +4°C and +40°C. For best performance the surfaces should be clean, dry, and grease free. The product should be unwound and lightly pressed into position leaving the release paper in place. On forming the joint the release paper is removed and the closing surface pushed firmly in place, pressure applied along the length of the joint and mechanically fixed.